

Amendments to th Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- 5 1. (Currently Amended) A method comprising:
- identifying partial feasible routing solutions corresponding to each of a subset of a set of wires to be routed, each of the partial feasible routing solutions identifying a feasible route between fixed points in a layout, at least two partial feasible routing solutions being identified for at least one of the wires to be
- 10 routed;
- constructing a routing tree from the identified partial feasible routing solutions for each of the subset of wires to be routed; and
- following identification of the partial feasible routing solutions, merging the partial feasible routing solutions trees to identify one or more feasible routing
- 15 solutions for the set of wires to be routed, wherein merging includes selecting between the identified partial feasible routing solutions for each of the subset of wires to identify a partial feasible routing solution that does not conflict with a
- selected partial feasible routing solution for any of the other wires of the subset of wires.
- 20
2. (Original) The method of claim 1 further comprising:
- selecting a routing solution from the feasible routing solutions.

3. (Original) The method of claim 1 further comprising:
sorting the identified partial feasible routing solutions and feasible routing solutions by a first user-selected cost function.

5 4. (Original) The method of claim 3 further comprising:
re-sorting the identified partial feasible routing solutions and feasible routing solutions by a second, different user-selected cost function.

5. (Original) The method of claim 1 further comprising:
10 limiting the number of partial feasible routing solutions identified to a first number; and
limiting the number of feasible routing solutions to a second number.

6. (Currently Amended) The method of claim 5 wherein merging
15 comprises:
merging partial feasible solutions in a routing tree, wherein, if an associated limitation is specified by a user, the number of partial feasible routing solutions at each node of the routing tree ~~may be~~ is limited according to a the user-specified limitation.

20

7. (Original) The method of claim 5 wherein identifying partial feasible routing solutions comprises:
generating Hanan's graph;

identifying a first partial feasible routing solution;
adding an obstacle to the first partial feasible routing solution; and
identifying a second, different partial feasible routing solution.

5 8. (Original) The method of claim 7 wherein adding an obstacle
and identifying a different partial feasible routing solution are repeated until there
are no more partial feasible routing solutions or until a user-specified limitation
on the number of partial feasible routing solutions has been reached, whichever
occurs first.

10

 9. (Previously Presented) A method comprising:
 constructing multiple partial feasible routing trees, each of the partial
feasible routing trees identifying a set of partial feasible routing solutions for a
subset of a set of wires to be routed, each of the partial feasible routing solutions
15 identifying feasible routes between fixed points in a layout; and
 merging the multiple partial feasible routing trees to identify a set of
feasible routing solutions for the set of wires to be routed.

 10. (Original) The method of claim 9 wherein constructing multiple
20 partial feasible routing trees comprises:
 determining partial feasible routing solutions for each of the subset of
wires to be routed until all partial feasible routing solutions have been identified

or until a user-specified limit on the number of partial feasible routing solutions has been reached, whichever occurs first.

11. (Original) The method of claim 10 wherein determining partial
5 feasible routing solutions comprises:

- generating Hanan's graph;
- identifying a first partial feasible routing solution;
- adding an obstacle to the first partial feasible routing solution; and
- identifying a second, different partial feasible routing solution.

10

12. (Original) The method of claim 10 further comprising:
determining a cost of each partial feasible routing solution according to a
first user-specified cost function; and
ordering the partial feasible routing solutions by the cost.

15

13. (Original) The method of claim 12 wherein merging comprises:
merging the partial feasible routing solutions in increasing order of cost
such that the feasible routing solutions are also ordered by cost.

20

14. (Original) The method of claim 13 further comprising:
re-ordering the partial feasible routing solutions and feasible routing
solutions according to a second user-specified cost function.

15. (Currently Amended) A method comprising:

determining a first set of possible routes between a first set of fixed points in an integrated circuit layout, the first set of possible routes being organized in a first routing tree;

5 determining a second set of possible routes between a second set of fixed points in the integrated circuit layout, the second set of possible routes being organized in a second routing tree; and

merging the first and second ~~sets of possible routes~~ routing trees to determine a third set of possible routes, the third set of possible routes including
10 possible routes from the first and second sets of possible routes that do not conflict.

16. (Original) The method of claim 15 further comprising:

ordering the first and second sets of possible routes by cost according to
15 a first user-specified cost function.

17. (Original) The method of claim 16 further comprising:

limiting the number of possible routes in the first, second and third sets according to one or more user-specified limitations.

20

18. (Original) The method of claim 15 wherein the first, second and third sets are organized as a routing tree, a root of the routing tree to include one or more possible routes for all wires to be routed.

19. (Original) The method of claim 16 further comprising:
reordering the possible routes by cost according to a second user-
specified cost function.

5 20. (Currently Amended) An apparatus comprising:
an integrated circuit device having wires routed according to a method
comprising:

identifying partial feasible routing solutions corresponding to each
of a subset of a set of wires to be routed, each of the partial feasible
10 routing solutions identifying a feasible route between two nodes fixed in
layout, at least two partial feasible routing solutions being identified for at
least one of the wires to be routed;

organizing the identified partial feasible routing solutions for each of
the subset of wires into a respective routing tree;

15 merging the ~~partial feasible routing solutions~~ routing trees to
identify one or more feasible routing solutions for the set of wires to be
routed, wherein merging includes selecting between the identified partial
feasible routing solutions for each of the subset of wires to identify a
partial feasible routing solution that does not conflict with a selected partial
20 feasible routing solution for any of the other wires of the subset of wires;

and

selecting the routing from the one or more feasible routing
solutions.

21. (Original) The apparatus of claim 20 wherein the method further comprises:

ordering the partial feasible routing solutions by cost according to one or more user-specified cost functions.

5

22. (Currently Amended) A data storage medium storing instructions to be executed by a computer system, the instructions comprising:

a maze router to determine partial feasible routing solutions for each of a subset of a set of wires to be routed, each of the partial feasible routing solutions
10 to identify a feasible route between fixed points in a layout, the maze router to identify at least two partial feasible routing solutions for at least one of the wires;

instructions to organize the partial feasible routing solutions for each of the subset of wires into a respective routing tree; and

a deferred merging router to merge the partial feasible routing solutions to
15 generate one or more feasible routing solutions, wherein merging includes selecting between the identified partial feasible routing solutions for each of the subset of wires to identify a partial feasible routing solution that does not conflict with a selected partial feasible routing solution for any of the other wires of the subset of wires.

20

23. (Original) The data storage medium of claim 22 further storing instructions comprising:

a first estimation engine to determine a first cost of each partial feasible routing solution and each feasible routing solution according to a first user-specified cost function,

the deferred merging router responsive to the first estimation engine to
5 order the partial feasible routing solutions and the feasible routing solutions by the first cost.

24. (Original) The data storage medium of claim 22 wherein the
maze router is responsive to a user-specified limitation to limit the number of
10 partial feasible routing solutions and feasible routing solutions determined for any of the subset of wires to be routed.

25. (Original) The data storage medium of claim 24 wherein the
deferred merging router organizes the partial feasible routing solutions in a
15 routing tree to identify the feasible routing solutions.

26. (Original) The data storage medium of claim 23 wherein
the deferred merging router is responsive to a second estimation engine
to re-order the partial feasible routing solutions and the one or more routing
20 solutions according to a second user-specified cost function.

27. (Currently Amended) A data storage medium storing instructions which, when executed by a computer system, cause the computer system to perform a method comprising:

identifying partial feasible routing solutions corresponding to each of a
5 subset of a set of wires to be routed, each of the partial feasible routing solutions
identifying a feasible route between points fixed in a layout, at least two partial
feasible routing solutions being identified for at least one of the wires to be
routed;

organizing the identified partial feasible routing solutions for each of the
10 subset of wires into a respective routing tree; and

merging the partial feasible routing ~~solutions~~ solution routing trees to
identify one or more feasible routing solutions for the set of wires to be routed,
wherein merging includes selecting between the identified partial feasible routing
solutions for each of the subset of wires to identify a partial feasible routing
15 solution that does not conflict with a selected partial feasible routing solution for
any of the other wires of the subset of wires.

28. (Original) The data storage medium of claim 27 further storing
instructions which, when executed by a computer system cause the computer
20 system to perform a method further comprising:

sorting the identified partial feasible routing solutions and feasible routing
solutions by a first user-selected cost function.

29. (Original) The data storage medium of claim 28 further storing instructions which, when executed by a computer system cause the computer system to perform a method further comprising:

re-sorting the identified partial feasible routing solutions and feasible
5 routing solutions by a second, different user-selected cost function.

30. (Original) The data storage medium of claim 27 further storing instructions which, when executed by a computer system cause the computer system to perform a method further comprising:

10 limiting the number of partial feasible routing solutions identified to a first number; and

limiting the number of feasible routing solutions to a second number.